

SAMPLE

検査成績表

<TEST REPORT>

1/2

品名<Model Name> (プログラマブルハイトスタ<PROGRAMABLE HiTESTER>)
 形名<Model Number> (3222)
 製造番号<Serial No.> (No. 110712345)
 検査年月日<Test Date> (2009-12-30)
 (<YYYY-MM-DD>)
 検査条件<Test Conditions> (25.0 °C, 50 %rh)
 検査周波数<Test Frequency> (50Hz)

項目 <Item>	ファンクション <Function>	レンジ <Range>	入力 <Input>	許容範囲 <Tolerance>	表示値 <Indicated Value>
確度					
<Accuracy>	DCV	200 mV	180.00 mV	179.91 mV ~ 180.09 mV	(179.91 mV)
		2000 mV	1800.0 mV	1799.1 mV ~ 1800.9 mV	(1799.1 mV)
		20 V	18.000 V	17.989 V ~ 18.011 V	(17.989 V)
		200 V	180.00 V	179.89 V ~ 180.11 V	(179.89 V)
		1000 V	1000.0 V	999.3 V ~ 1000.7 V	(999.3 V)
	ACV	200 mV	180.00 mV	179.16 mV ~ 180.84 mV	(179.16 mV)
		2000 mV	1800.0 mV	1791.6 mV ~ 1808.4 mV	(1791.6 mV)
		20 V	18.000 V	17.916 V ~ 18.084 V	(17.916 V)
		200 V	180.00 V	179.16 V ~ 180.84 V	(179.16 V)
		750 V	750.0 V	739.5 V ~ 760.5 V	(739.5 V)
Ω		200 Ω	100.00 Ω	99.91 Ω ~ 100.09 Ω	(99.91 Ω)
		2000 Ω	1000.0 Ω	999.1 Ω ~ 1000.9 Ω	(999.1 Ω)
		20 kΩ	10.000 kΩ	9.991 kΩ ~ 10.009 kΩ	(9.991 kΩ)
		200 kΩ	100.00 kΩ	99.91 kΩ ~ 100.09 kΩ	(99.91 kΩ)
		2 MΩ	1.0000 MΩ	0.9985 MΩ ~ 1.0015 MΩ	(0.9985 MΩ)
		20 MΩ	10.000 MΩ	9.940 MΩ ~ 10.060 MΩ	(9.940 MΩ)
		200 MΩ	100.0 MΩ	94.0 MΩ ~ 106.0 MΩ	(94.0 MΩ)

備考<Note>

FAIL判定箇所は、グレー表示としています。<FAIL decision points are highlighted in gray.>

総合判定<Overall Result>	検査者<Inspected by>	承認者<Approved by>
(PASS)	()	()

No.3222-3

SAMPLE

検査成績表

<TEST REPORT>

2/2

製造番号<Serial No.> (No. 110712345)
検査年月日<Test Date> (2009-12-30)
<YYYY-MM-DD>

項目 <Item>	ファンクション <Function>	レンジ <Range>	入力 <Input>	許容範囲 <Tolerance>	表示値 <Indicated Value>
確度					
<Accuracy>	DCA	200 uA	180.00 uA	179.23 uA ~ 180.77 uA	(179.23 uA)
		2000 uA	1800.0 uA	1797.1 uA ~ 1802.9 uA	(1797.1 uA)
		20 mA	18.000 mA	17.923 mA ~ 18.077 mA	(17.923 mA)
		200 mA	180.00 mA	179.71 mA ~ 180.29 mA	(179.71 mA)
		2 A	1.8000 A	1.7887 A ~ 1.8113 A	(1.7887 A)
		10 A	10.000 A	9.955 A ~ 10.045 A	(9.955 A)
	ACA	200 uA	180.00 uA	178.34 uA ~ 181.66 uA	(178.34 uA)
		2000 uA	1800.0 uA	1788.8 uA ~ 1811.2 uA	(1788.8 uA)
		20 mA	18.000 mA	17.834 mA ~ 18.166 mA	(17.834 mA)
		200 mA	180.00 mA	178.88 mA ~ 181.12 mA	(178.88 mA)
		2 A	1.8000 A	1.7798 A ~ 1.8202 A	(1.7798 A)
		10 A	10.000 A	9.890 A ~ 10.110 A	(9.890 A)
	Hz	200 Hz	100.00 Hz	99.96 Hz ~ 100.04 Hz	(99.96 Hz)
		2000 Hz	1000.0 Hz	999.6 Hz ~ 1000.4 Hz	(999.6 Hz)
		20 kHz	10.000 kHz	9.998 kHz ~ 10.002 kHz	(9.998 kHz)
		200 kHz	100.00 kHz	99.98 kHz ~ 100.02 kHz	(99.98 kHz)

No.3222-3