

SAMPLE

## 検査成績表

&lt;TEST REPORT&gt;

HIOKI  
HIOKI E. E. CORPORATION

1/1

品名<Model Name> ( デジタルハイテスタ<DIGITAL HiTESTER> )  
形名<Model Number> ( 3235 )  
製造番号<Serial No.> ( No. )  
検査年月日<Test Date> ( <YYYY-MM-DD> )  
検査条件<Test Conditions> ( °C, %rh )  
検査周波数 ( 50 Hz )  
<Test Frequency>

| 項目<br>＜Item＞ | レンジ<br>＜Range＞ |     | 入力<br>＜Input＞ |        | 許容範囲<br>＜Tolerance＞ |        |     |   | 表示値<br>＜Indication＞ |       |             |
|--------------|----------------|-----|---------------|--------|---------------------|--------|-----|---|---------------------|-------|-------------|
| 精度＜Accuracy＞ |                |     |               |        |                     |        |     |   |                     |       |             |
| DC V         | 300            | mV  |               | 290.00 | mV                  | 289.90 | mV  | ～ | 290.10              | mV (  | 289.90 mV)  |
|              | 3              | V   |               | 2.9000 | V                   | 2.8984 | V   | ～ | 2.9016              | V (   | 2.8984 V)   |
|              | 30             | V   |               | 29.000 | V                   | 28.984 | V   | ～ | 29.016              | V (   | 28.984 V)   |
|              | 300            | V   |               | 290.00 | V                   | 289.84 | V   | ～ | 290.16              | V (   | 289.84 V)   |
|              | 1000           | V   |               | 1000.0 | V                   | 999.3  | V   | ～ | 1000.7              | V (   | 999.3 V)    |
| AC V         | 3              | V   | 20kHz         | 2.9000 | V                   | 2.8670 | V   | ～ | 2.9330              | V (   | 2.8670 V)   |
|              | 3              | V   |               | 2.9000 | V                   | 2.8854 | V   | ～ | 2.9146              | V (   | 2.8854 V)   |
|              | 30             | V   |               | 29.000 | V                   | 28.854 | V   | ～ | 29.146              | V (   | 28.854 V)   |
|              | 300            | V   |               | 290.00 | V                   | 288.54 | V   | ～ | 291.46              | V (   | 288.54 V)   |
|              | 750            | V   |               | 750.0  | V                   | 739.5  | V   | ～ | 760.5               | V (   | 739.5 V)    |
| DC A         | 300            | mA  |               | 290.00 | mA                  | 288.53 | mA  | ～ | 291.47              | mA (  | 288.53 mA)  |
|              | 1000           | mA  |               | 1000.0 | mA                  | 994.8  | mA  | ～ | 1005.2              | mA (  | 994.8 mA)   |
| AC A         | 300            | mA  |               | 290.00 | mA                  | 285.25 | mA  | ～ | 294.75              | mA (  | 285.25 mA)  |
|              | 1000           | mA  |               | 1000.0 | mA                  | 981.0  | mA  | ～ | 1019.0              | mA (  | 981.0 mA)   |
| Ω            | 300            | Ω   |               | 290.00 | Ω                   | 289.66 | Ω   | ～ | 290.34              | Ω (   | 289.66 Ω)   |
|              | 3              | kΩ  |               | 2.9000 | kΩ                  | 2.8978 | kΩ  | ～ | 2.9022              | kΩ (  | 2.8978 kΩ)  |
|              | 30             | kΩ  |               | 29.000 | kΩ                  | 28.978 | kΩ  | ～ | 29.022              | kΩ (  | 28.978 kΩ)  |
|              | 300            | kΩ  |               | 290.00 | kΩ                  | 289.78 | kΩ  | ～ | 290.22              | kΩ (  | 289.78 kΩ)  |
|              | 3000           | kΩ  |               | 2900.0 | kΩ                  | 2896.9 | kΩ  | ～ | 2903.1              | kΩ (  | 2896.9 kΩ)  |
|              | 30             | MΩ  |               | 29.000 | MΩ                  | 28.908 | MΩ  | ～ | 29.092              | MΩ (  | 28.908 MΩ)  |
| FREQUENCY    | 1000           | Hz  | 5V            | 900.00 | Hz                  | 899.80 | Hz  | ～ | 900.20              | Hz (  | 899.80 Hz)  |
|              | 10             | kHz | 5V            | 9.0000 | kHz                 | 8.9980 | kHz | ～ | 9.0020              | kHz ( | 8.9980 kHz) |
|              | 100            | kHz | 5V            | 90.000 | kHz                 | 89.980 | kHz | ～ | 90.020              | kHz ( | 89.980 kHz) |
|              | 300            | kHz | 5V            | 290.00 | kHz                 | 289.93 | kHz | ～ | 290.07              | kHz ( | 289.93 kHz) |

## 備考&lt;Note&gt;

FAIL判定箇所は、グレー表示としています。&lt;FAIL decision points are highlighted in gray.&gt;

| 総合判定<Overall Result> | 検査者<Inspected by> | 承認者<Approved by> |
|----------------------|-------------------|------------------|
| ( PASS )             | ( )               | ( )              |

No.3235-8