

Quick Comparison of HIOKI PQAs

	PQ3198	PW3198 <i>Discontinued</i>	PQ3100
IEC 61000-4-30	Class A	Class A	Class S
Current sensor terminals	HIOKI PL14 (14-pin dedicated)	BNC	HIOKI PL14 (14-pin dedicated)
Power supply to flexible and AC/DC current sensors	Available	Not available	Available
Event items	Basic and advanced events	Basic and advanced events	Basic events only
Transient overvoltage	2MS/S, 6kV	2MS/S, 6kV	200kS/s, 2.2kV
High-order harmonics	Available	Available	Not available
PC software	PQ One (bundled)	9624-50 (option)	PQ One (bundled)
Max. number of events	9999 events	1000 events	9999 events
Repeat measurement	366 times	55 times	366 times
Display languages	10 languages	3 languages	10 languages
Kit models	<p>PQ3198-92 600A sensor (4) and other options</p> <p>PQ3198-94 6000A flexible sensor (4) and other options</p>	<p>PW3198-90 Set with PQA HiVEW 9624-50 (without current sensor, case, etc.)</p>	<p>PQ3100-91 600A sensor (2) and other options</p> <p>PQ3100-92 600A sensor (4) and other options</p> <p>PQ3100-94 6000A flexible sensor (4) and other options</p>